



Kaagapay ng Komunidad sa Maginhawang Pamumuhay



Standard Form Number: SF-GOOD-60

Revised on: January 08, 2018

Standard Form Title: **Request For Quotation**

Company Name: \_\_\_\_\_

Date: \_\_\_\_\_

Address: \_\_\_\_\_

Quotation No.: 2023051500075

PhiGEPS Reg. No. \_\_\_\_\_

Please quote you lowest price on the item/s listed below, subject to the General Conditions, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than \_\_\_\_\_, 2023.

MARY GRACE D. MANGAO

DATA ENCODER

Tel/Fax No.: (02) 8817-3168

**General Conditions:**

1. All entries must be typewritten/accurate/readable.
  2. Delivery period must be within seven (7) calendar days only.
  3. Warranty shall be for a period of six (6) months for supplies and materials, one (1) year for equipment, from the date of acceptance by the Procuring Entity.
  4. Price validity must be within thirty (30) calendar days.
  5. Bidders must submit Certificate of PhilGEPS registration, updated Business Permit/Mayor's Permit, Notarized Omnibus Sworn Statement (for ABC's above 50k), and Income or Business Tax Return for ABC's above 500k.
  6. Bidders shall submit original brochures showing specifications of product being offered.
  7. All bid proposals must be VAT inclusive.
- (FAILURE TO DO SO WILL MEAN DISQUALIFICATION OF YOUR BID PROPOSAL.)**

Item No.	Item and Description	QTY	Approved Budget (In Php)	BID Price
A-002-027	<p>Audio Conferencing System-Supply, Delivery and Installation of Conferencing System</p> <p>NETWORK VIDEO ENDPOINT (CORE CAPABLE) (1 unit)            Core Mode            Fully integrated Q-SYS Core processor            On board 3 x 2 HDMI video switcher            32 x 32 network audio channels            Supports up to 32 x 32 software-based dante channels (none included)            8x AEC channels            Supports up to three (3) Q-SYS NM-T1 tabletop microphones            1x VoIP softphoned instance            Audio I/O via HDMI, USB and 3.5mm            Peripheral mode            Native HDMI video and audio distribution for Q-SYS            Q-SYS shift™ adaptive video compression codec            Software-configurable as an encoder or decoder            Simultaneous streaming capabilities            Audio            Networ audio: use a total network channel count of 40x32, including Q-SYS native audio channels or dante channels (licensable up to 32x32)            HDMI audio input: each HDMI input is able to receive up to eight channels of PCM audio, which are routable within Q-SYS designer software</p> <p>NETWORK AUDIO I/O EXPANDERS (1 unit)            Two (2) mic/line inputs and two (2) line outputs            Professional mic/line level inputs with +48 VDC phantom power and/or line outputs            Microphone detection on inputs enables monitoring, usage statistics, and failure notifications            Power-over-ethernet capable            Daisy-chain up to four QIO network I/O expanders on a single network run (with local daisy-chained DC power)            Simple drag-and-drop integration and comprehensive management via Q-SYS designer software and Q-SYS reflect enterprise manager            Surface- or rack-mountable</p>	1	980,000.00	

Includes surface mounting hardware  
Other Connectors  
External power supply 24 VDC nominal, 2.5A on euro connector with second connector for daisy-chaining (QIO-PSU power supply sold separately)  
LAN (PoE) gigabit LAN connection for Q-LAN, PoE  
PoE specification conforms to IEEE 802.3af Type 1  
Lan (Thru) ethernet daisy-chaining

PROFESSIONAL AMPLIFIERS (1 unit)  
Up to 200 watts per channel into 4 and 8 ohms  
Energy star qualified amplifier  
Bridgeable outputs for higher power  
Channels2  
Stereo Mode (all channels driven)  
8Ω - 200W  
4Ω - 200W  
Bridged outputs (all channels driven)  
8Ω & 4Ω - 400W  
70V - 350W  
100V - 350W  
200W  
Frequency response (4Ω and 8Ω) 20Hz-20KHz +/-0.1 dB  
Signal to noise (20Hz - 20KHz) >100dB  
Input sensitivity 1.23V (+4 dBu)

IN-CEILING LOUDSPEAKERS (4 PAIRS)  
Full-range 2.25-inch transducer, low frequency range down to 83Hz, 16-ohm, and 70/100V operation  
Front baffle-mounted tap settings and front-baffle audio connections  
Pick your power - FS2 models feature a 2.25inch full-range transducer, low frequency down to 83Hz,16-ohm and 700/100V operation  
Maintain consistent tonal quality with shared voicing across all FS models  
Hear the best of both music and voice with transducers that offer clear voice reproduction and smooth response for background music

MANAGED POE SWITCH (1 UNIT)  
Console port Cisco Standard mini USB Type-B / RJ45 console port  
USB slot USB Type-A slot on the front panel of the switch for easy file and image management  
Buttons reset button  
Cabling type Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T  
LEDs System, Link/Act, PoE, Speed  
Flash 256MB  
CPU 800MHz ARM  
DRAM 512MB  
10 Gigabit Ethernet,  
8 Gigabit Ethernet 2 Gigabit Ethernet Combo  
Console port Cisco Standard mini USB Type-B / RJ45 console port  
USB slot USB Type-A slot on the front panel of the switch for easy file and image management  
Unit Weight & Dimension: 3.5kg (7.72lb), 268 x 185 x44mm (10.56x7.28x1.73in)

CONFERENCING SYSTEM CENTRAL UNIT (1 UNIT)  
Record & play function thru USB or SD card  
Equipped with 3 groups + extension group for system connecting workable  
For 20 mic units each group  
Output level LED indicator  
Single, multiple and many groups can be use simultaneously  
Line volume for the unit source  
Mic volume for the external Mic connection  
Master volume control the mic line level  
Balance XLR output  
Extension to other main unit in case will use more than 60 pieces

CONFERENCING CHAIRMAN'S UNIT (1 unit)  
Priority buttons  
Mic on/off buttons  
Built in 2W speaker  
Volume control  
Unidirectional condenser mic  
Red light indicate mic is on

	<p>CONFERENCE DELEGATE UNIT (16 UNITS)  Mic on/off buttons  Built in 2W speaker  Volume control  Unidirectional condenser mic  Red light indicate mic is on</p> <p>CONFERENCE NETWORK CABLE ASSEMBLY (1 UNIT)  Cable length (M): 10m  8 pin XLR female for conference cable mic  8 pin XLR male for conference cable mic</p> <p>CONFERENCE NETWORK CABLE ASSEMBLY (1 UNIT)  Cable length (M): 5m  8 pin XLR female for conference cable mic  8 pin XLR male for conference cable mic</p> <p>HDMI EXTENDER - TRANSMITTER (1 UNIT)  Pairs with a DM Lite® or DMPS Lite™ receiver  Enables extension of HDMI® video and audio signals  Links to the receiver via a single CAT5e (or higher) twisted pair cable  Supports 4K and UHD at up to 130 ft (40m)  Supports HD 1080p, WUXGA, and 2K at up to 230ft (70m)  Handles 4K video resolutions up to 4K60 4:2:0 and 4K30 4:4:4  Handles 3D video and deep color  Supports Dolby® TrueHD, Dolby Atmos®, DTS HD®, DTS:X®, and uncompressed 7.1 linear PCM audio  Compatible with HDMI, DVI, and dual-mode display port™ sources  HDCP 2.2 compliant  Passes CEC and EDID signals</p> <p>HDMI EXTENDER - RECEIVER (1 UNIT)  Pairs with a DM Lite transmitter to provide a simple point-to-point signal extender  Enables extension of HDMI® video and audio signals  Links to the transmitter via a single CAT5e (or better) twisted pair cable [1]  Supports 4K and UHD at up to 130 ft (40m)  Supports HD 1080p, WUXGA, and 2K at up to 230ft (70m)  Handles 4K video resolutions up to 4K60 4:2:0 and 4K30 4:4:4  Handles 3D video and deep color  Supports Dolby® TrueHD, Dolby Atmos®, DTS HD®, DTS:X®, and uncompressed 7.1 linear PCM audio  Compatible with HDMI and DVI display devices [3]  HDCP 2.2 compliant  Passes CEC and EDID signals</p> <p>75-INCHES, 4K ULTRA HD SMART TV (1 UNIT)  Display  75 inch display, LED screen, 4K resolution, 3840 x 2160 pixels, 60 Hz refreshrate, 178° viewing angle  Audio  2 speakers  20w speaker output  Connectivity  3 HDMI ports, 2 usb ports, 1 headphone port, ethernet  Smart Features  Screen Mirroring, Wifi, Bluetooth, a5 gen5 al processor 4K  Remote Features  Internet access on remote</p> <p>AV EQUIPMENT RACK (1 UNIT)  19 inch equipment racks  12 rack space versions  Heavy duty steel construction with fully enclosed sides  3 inch (75mm) locking casters  Single space blank panel included  U.S. and European rack screws included</p> <p>CEILING BRACKET  Customized ceiling bracket for 75" TV</p> <p>Programming</p> <p>Labor, Engineering Materials, General Services and Installation</p>			
	<p><b>Place of Delivery:</b> 8737 BDO PLAZA PASEO DE ROXAS  MAKATI CITY</p> <p><b>Delivery Term:</b> FOB Destination</p>		<p><b>980,000.00</b></p>	

**Term of Payment:** 15 working days upon complete delivery

**Brand and Model:** \_\_\_\_\_

**Delivery Period:** \_\_\_\_\_

**Warranty:** \_\_\_\_\_

**Price Validity:** \_\_\_\_\_

**Payee's Name & TIN:** \_\_\_\_\_

After having carefully read and accepted your General Conditions, I/We quote you on the item at prices noted above.

\_\_\_\_\_  
Printed Name / Signature

\_\_\_\_\_  
Tel. No. / Cellphone No

\_\_\_\_\_  
E-mail Address

\_\_\_\_\_  
Date